



## INFO

Capacity, working length and width designed on individual customer requirements.

The spreader beams can be combined with the different suspension types, see pages 216 - 217.



## INFO

Capacity, working length and width designed on individual customer requirements.

The spreader beams can be combined with the different suspension types, see pages 216 - 217.

## TTS-HE H-frame spreader beam

**Capacity up to 10000 kg**

For the transport of symmetrical loads.

### Features

- Lifting brackets for single hook according to DIN 15401
- Eyehooks with forged safety latch

### Optional

- Accentral suspension for asymmetrical loads

### Technical questionnaire

Capacity \_\_\_\_\_ kg

Working length \_\_\_\_\_ mm

Working width \_\_\_\_\_ mm

## TTS-H H-frame spreader beam

**Capacity up to 25000 kg**

For the transport of symmetrical and asymmetrical loads.

### Features

- Lifting brackets for single hook according to DIN 15401
- Adjustment with grids
- Adjustable bracket with handle and swivel hook (cannot be rotated under load)

### Technical questionnaire

Capacity \_\_\_\_\_ kg

Working length, min. \_\_\_\_\_ mm

Working length, max. \_\_\_\_\_ mm

Working width, min. \_\_\_\_\_ mm

Working width, max. \_\_\_\_\_ mm